



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX BVS 16.0066** Page 1 of 5 [Certificate history:](#)
Issue 0 (2016-09-27)

Status: **Current** Issue No: 1

Date of Issue: 2022-03-29

Applicant: **R. STAHL Schaltgeräte GmbH**
Am Bahnhof 30
74638 Waldenburg
Germany

Equipment: **Position switch type 8060/2-*.*.***

Optional accessory:

Type of Protection: **Flameproof Enclosures "d", Protection by Enclosure "t", Increased Safety "e"**

Marking: **Ex db eb IIC T6 Gb**
Ex tb IIIC T80°C Db

Approved for issue on behalf of the IECEx
Certification Body:

Dr Franz Eickhoff

Position:

Lead Auditor and officially recognised expert

Signature:
(for printed version)

Date:
(for printed version)

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

DEKRA Testing and Certification GmbH
Certification Body
Dinnendahlstrasse 9
44809 Bochum
Germany

 **DEKRA**
On the safe side.



IECEX Certificate of Conformity

Certificate No.: **IECEX BVS 16.0066**

Page 2 of 5

Date of issue: 2022-03-29

Issue No: 1

Manufacturer: **R. STAHL Schaltgeräte GmbH**
Am Bahnhof 30
74638 Waldenburg
Germany

Manufacturing locations: **R. STAHL Schaltgeräte GmbH**
Am Bahnhof 30
74638 Waldenburg
Germany

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

[IEC 60079-1:2014-06](#) Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
Edition:7.0

[IEC 60079-31:2013](#) Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Edition:2

[IEC 60079-7:2017](#) Explosive atmospheres - Part 7: Equipment protection by increased safety "e"
Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[DE/BVS/ExTR16.0065/01](#)

Quality Assessment Report:

[DE/BVS/QAR10.0002/17](#)



IECEX Certificate of Conformity

Certificate No.: **IECEX BVS 16.0066**

Page 3 of 5

Date of issue: 2022-03-29

Issue No: 1

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

Subject and Type

Position switch type 8060/2-*-*

- | | |
|-------------|---------------------------------|
| 1. Asterisk | Contact |
| 2. Asterisk | Actuator |
| 3. Asterisk | Lower ambient temperature range |

Description

The position switch 8060/2-*-* is designed in type of protection Increased Safety "e" and Protection by Enclosure "t" and is equipped with a switch type 8080/1-* (IECEX PTB 05.0025 U), type Ex 95... (IECEX BVS 16.0009U) or type Ex E* 04.93** (IECEX BVS 16.0069U) in type of protection Flameproof Enclosure "d".

The position switch is suitable for the application in areas potentially hazardous by combustible gases and dusts.

Listing of all components used referring to older standards

Subject and type	Certificate	Standards
Switch type 8080/1-*	IECEX PTB 05.0025 U	IEC 60079-0:2011 IEC 60079-1:2007 ¹ IEC 60079-7:2006 ¹
Switch type Ex 95...	IECEX BVS 16.0009U	IEC 60079-0:2011 ¹ IEC 60079-1:2014
Switch type Ex E* 04.93**	IECEX BVS 16.0069U	IEC 60079-0:2011 ¹ IEC 60079-1:2014

¹ No applicable technical differences

SPECIFIC CONDITIONS OF USE: NO



IECEX Certificate of Conformity

Certificate No.: **IECEX BVS 16.0066**

Page 4 of 5

Date of issue: 2022-03-29

Issue No: 1

Equipment (continued):

Parameters

With switch type 8080/1-* (IECEX PTB 05.0025 U)

Rated switching voltage	AC	500 V
Rated switching current		2 A
	or	4 A
Utilization category	AC	15
Rated connecting capacity		1.5 mm ²
Ambient temperature range		
For 4 A		-20 °C / -40 °C / -60 °C up to +55 °C
For 2 A		-20 °C / -40 °C / -60 °C up to +60 °C
Degree of protection	IP66 (IP67 for -20 °C up to +55 °C / +60 °C)	

With switch type Ex 95... (IECEX BVS 16.0009U)

Rated switching voltage	AC	250 V
Rated switching current		3 A
	or	6 A
Utilization category	AC	15
Rated connecting capacity		1.5 mm ²
Ambient temperature range		
For 6 A		-20 °C up to +45 °C
For 3 A		-20 °C up to +60 °C
Degree of protection	IP67	

With switch type Ex E* 04.93** (IECEX BVS 16.0069U)

Rated switching voltage	AC	250 V
Rated switching current		1.5 A
Utilization category	AC	15
Rated connecting capacity		1.5 mm ²
Ambient temperature range		-20 °C up to +60 °C

Degree of protection IP67



IECEX Certificate of Conformity

Certificate No.: **IECEX BVS 16.0066**

Page 5 of 5

Date of issue: 2022-03-29

Issue No: 1

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

- Optionally use of the switches type Ex 95... or type Ex E* 04.93**
- Optionally use of 2 new actuators type WHKR and WHKD
- Extension of the ambient temperature range
- Update to the current version of the standard