





- > High degree of protection, IP66/67 standard, IP68 can be delivered upon request
- > Drainage flange in box prevents penetration of water
- > Manufactured in acid proof stainless steel (AISI 316L)
- > Tailor made size and performance is possible
- > Stainless steel type label spot welded to the cover
- > Several earthing alternatives
- > Maximum strength and corrosion resistance
- > Low lifetime maintenance cost














	ATEX					
Zone	0	1	2	20	21	22
For use in		х	x			

## **Explosion Protection**

Marking		
Europe (ATEX)		
Certificates		
Europe (ATEX)	NEMKO 01ATEX097 CSA 216432	

WebCode T1058E

Series TEF 1058



Selection	Table
Selection	Iable

Selection Table Version	Picture	Equipped with	Order number
Junction box for heat tracing with 4 pc. dia 25 mm entries	14052E00	1 x Transition unit TEF 7721 with M25 entry 4 x Terminals PHOENIX MXK 4 E 2 x Terminals PHOENIX MBK 6/E 4 x Dia 25 mm entries for power cable in junction box	TEF10581006
Junction box for heat tracing with 3 pc. dia 25 mm entries	14052E00	1 x Transition unit TEF 7721 with M25 entry 4 x Terminals PHOENIX MXK 4 E 2 x Terminals PHOENIX MBK 6/E 3 x Dia 25 mm entries for power cable in junction box	TEF10580506
Junction box for heat tracing with 1 pc. cable gland, 1 pc. stopping plug and 1 pc. drainplug	14053E00	1 x Transition unit TEF 7721 with M25 entry 2 x Cable glands for power cable type: E204/3B/M25 1 x Stopping plug M25, brass 4 x Terminals PHOENIX MXK 4 Ex 2 x Terminals PHOENIX MBK 6/E 1 x Trafolyte lable	TEF9177089
Junction box for heat tracing with 5 pc. dia 25 mm entries	14054E00	2 x Transition unit TEF 7721 with M25 entry 6 x Terminals PHOENIX UK6N 5 x Dia 25 mm entries for power cable in junction box	TEF10581506
Junction box for heat tracing with 5 pc. dia 25 mm entries	14055E00	1 x Transition unit TEF 7720D, SS316L with M25 stopping plugs (brass) 5 x Dia 25 mm entries with stopping plugs (brass) in junction box 10 x Terminals PHOENIX UK6N 1 x Trafolyte lable 1 pair adaptor for 3" pipe or larger, SS316L	TEF9177008

Series TEF 1058





## **Selection Table**

Version	Picture	Equipped with	Order number
Junction box for heat tracing with 2 pc. cable gland, 1 pc. stopping plug and 1 pc. drainplug	14056E	2 x Transition unit TEF 7721 with M25 entries 2 x Cable glands for power cable type: E204/3B/M25 2 x Stopping plugs M25, brass 9 x Terminals PHOENIX UK6N 1 x Trafolyte lable 1 x Drainplug M25	TEF9177091

Technical Data				
Electrical data				
Rated voltage	Voltage	420 V (max. 4 mm <sup>2</sup> )	750 V (max. 10 mm <sup>2</sup> )	
	Junction box	TEF10581006	TEF10581506	
		TEF10580506	TEF9177008	
		TEF9177089	TEF9117091	
Mechanical data				
Enclosure material	Material	AISI 316L / EN1.4404 Bright chemical dip	AISI 316L / EN1.4404 Electro polished	
	Junction box	TEF10581006	TEF9177008	
		TEF10580506		
		TEF9177089		
		TEF10581506		
		TEF9117091		
Degree of protection	IP66 / IP67			


## **Accessories and Spare Parts**

Designation	Description	Order number
Connection kit	for Thermon cables KSX and HTSX, gasket 5 x 11	TEF9177223
	for Thermon cables BSX and VSX, gasket 5 x 13	TEF9177217
	for Thermon cables TSX and RSX, gasket 5 x 15	TEF9177218
Cable gland for power cable	E204 / 3B / M25 - 9 mm; Ø 13 17.1 mm; with lock nut	TEF9147118
	E204 / 3A / M25 - 9 mm; Ø 14.1 20.1 mm; with lock nut	TEF9147119
Stopping plug	M25 - 9 mm; with lock nut	TEF9147113
Drain plug	M25 - 9 mm; with lock nut	TEF7302106

Series TEF 1058



## Dimensional Drawings (All Dimensions in mm) - Subject to Alterations




Series TEF 1058





## Dimensional Drawings (All Dimensions in mm) - Subject to Alterations



We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.