

## Linear luminaire With LED GRP



### Technical Data

#### General:

Product Type: 6402/4144-9100-152-2220-22-850S

#### Explosion Protection:

IECEX gas explosion protection: Ex ec IIC T4 Gc

IECEX dust explosion protection: Ex tb op is / tc IIIC T100 °C Db

ATEX gas explosion protection: II 3 G Ex ec IIC T4 Gc

ATEX dust explosion protection: II 2 D Ex tb op is / tc IIIC T100 °C Db

Certificates: ATEX (IBE), IECEX (IBE)

Declaration of Conformity: ATEX (EUK), Declaration of Conformity (AUS)

#### Electrical Data:

Rated operational voltage AC:

Rated operational voltage DC: 196 ... 250 V

Frequency range: 50 – 60 Hz

#### Ambient Conditions:

Ambient temperature: -40 °C ... +50 °C (T100 °C) Note: Through wiring Max. 3x16 A -40 °C ... +55 °C (T100 °C) Note: Through wiring 2 Max. 3x10 A

#### Lighting Data:

Number of lamps: 1

Lamp wattage: 42 W

Lamp: LED

Light colour: 5000 K – neutral white

Light distribution: 120°x120°

Luminaire efficacy: 121 lm/W

Luminous flux: 5100 lm

Colour rendering: ≥ 80

#### Mechanical Data:

Translucent cover: Translucent

IP degree of protection (IEC 60598): IP66/IP67

Enclosure material: Polyester resin, Glass fibre reinforced

Enclosure colour: Light grey (RAL 7035)

Diffuser: Without diffuser

Sealing material: Silicone

Max. solid connection terminals: 6 mm<sup>2</sup>

Max. finely stranded connection terminals: 4 mm<sup>2</sup>

Type of connection cable: Finely stranded Solid

Size: 4

Impact strength (IEC 62262): IK10

Disconnection of the luminaire: No



**Components:**

Threaded plate: 2x SS430 stainless steel

Ballast: CG Luxtronic 48 W 300mA (91)

Through wiring: With 5 conductors 2.5 mm<sup>2</sup>

Drilled holes: 3 x M20

Example Type: 6402/4144-9100-152-2220-22-850S | Art. No. 310117

Manufacturer: R. STAHL Schaltgeräte GmbH | Am Bahnhof 30 | 74638 WALDENBURG | [r-stahl.com](http://r-stahl.com)